## **GlobalThin GN046TH**



## TECHNICAL DATA SHEET

## **Epoxy Shop-primer Fast Thinner**

PRODUCT DESCRIPTION	◆ GlobalThin GN046TH is a fast thinner for epoxy shop primers.		
PERFORMANCES	<ul> <li>Good dilution properties and fast evaporation for epoxy shop primers, according with the technical data sheets of each product;</li> <li>Good cleaning power for a wide range of products.</li> </ul>		
RECOMMENDED USE	THINNER Use recommended for the following products (see product TDS): GN131SP. CLEANING: Use recommended for the following products: GN131SP. However, Globalnavy advice to choose the most environmentally friendly cleaning solvent.		
APPROVALS			
COMPONENT A	COMPONENT B	COLOURS	
GN046TH	NA	Transparent.	
Physical Properties			
GLOSS	NA		
SOLIDS BY VOLUME	0% .		
VOC*	820 g/Lt.		
FLASH POINT	-4°C (25°F) Setaflash		
PERFORMANCE			
Application			
SURFACE PREPARATION	NA		
APPLICATION METHOD	NA		
APPLICATION CONDITIONS	NA		
APPLICATION DATA	Use GlobalThin GN046TH only on well ventilated areas. Highly flammable product. Be aware to use equipment grounding in order to dissipate electrostatic charges.		
MIX RATIO	NA		
HARDENER	NA		
POT LIFE	NA		
THINNER	NA		
SOLVENT / CLEANER	NA		
DRY TIME	NA		

## GlobalThin GN046TH



PERFORMANCE IN COATINGS

THEORETICAL COVERAGE	NA
TYPICAL PAINT SYSTEM	NA
STORAGE	4 years (storage on the original tightly closed containers in a dry, cool, well ventilated space, at temperatures between $5^{\circ}$ C - $40^{\circ}$ C).
PACKING	Available in 1 L, 5 L, 25L.
FURTHER INFORMATION	NA
HEALTH SAFETY	Please take the necessary measures in order to accomplish the national laws and regulations regarding the environmental, health and safety at work. Please observe the safety information displayed on the container. Please refer to the Safety Data Sheet for detailed information on the health, safety hazards and precautions for the use of this product.

The information on this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. This is not a specification and all information is given in good faith. Every values presented as Theoretical were calculated from the product formula, so can have deviation from laboratory measurements using standard methods that may be not applicable. However, since the product can be used under conditions beyond our control, the manner of use is the sole responsibility of the user. The product is intended for professional use only. Manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. This Technical Data Sheet content can be changed without notice.

Parque Industrial de Carrascas, Estrada Nacional 252, 2950-402 Palmela PORTUGAL 

◆ Tel.:+351 265107979 

◆ www.globalnavy.net 

◆ email: sales@globalnavy.net