## **GlobalThin GN077TH**



## TECHNICAL DATA SHEET

## **Cellulosic Thinner**

| PRODUCT DESCRIPTION    | ♦ GlobalThin GN077TH is a cellulosic thinner.  |              |  |
|------------------------|--|--------------|--|
| PERFORMANCES           | <ul> <li>Good dilution properties for a wide different kind of paints, according with the technical data sheets of each product.</li> <li>Good cleaning power for a wide range of products.</li> </ul>   |              |  |
| RECOMMENDED USE        | THINNER  Use recommended for the following products (see product TDS): GN400AV / GN410AP / GN500.  CLEANING: Use recommended for the following products: GN002HT / GN012HT / GN101 / GN133 / GN2 /GN400 /GN410 / GN500 / GN550 /GN560 . However, Globalnavy advice to choose the most environmentally friendly cleaning solvent. |              |  |
| APPROVALS              |  |              |  |
| COMPONENT A            | COMPONENT B  | COLOURS      |  |
| GN077TH                | NA   | Transparent. |  |
| Physical Properties    |  |              |  |
| GLOSS                  | NA   |              |  |
| SOLIDS BY VOLUME       | 0%.  |              |  |
| VOC*                   | 860 g/Lt.  |              |  |
| FLASH POINT            | 12°C (54°F) Setaflash.   |              |  |
| PERFORMANCE            |  |              |  |
| Application            |  |              |  |
| SURFACE PREPARATION    | NA   |              |  |
| APPLICATION METHOD     | NA   |              |  |
| APPLICATION CONDITIONS | NA   |              |  |
| APPLICATION DATA       | Use GlobalThin GN077TH only on well ventilated areas. Highly flammable product. Be aware to use equipment grounding in order to dissipate electrostatic charges.   |              |  |
| MIX RATIO              | NA   |              |  |
| HARDENER               | NA   |              |  |
| POT LIFE               | NA   |              |  |
| THINNER                | NA   |              |  |
| SOLVENT / CLEANER      | NA   |              |  |

## GlobalThin GN077TH

NA

**DRY TIME** 



PERFORMANCE IN COATINGS

| THEORETICAL COVERAGE | NA  |  |
|----------------------|---|--|
| TYPICAL PAINT SYSTEM | NA  |  |
| STORAGE              | 2 years (storage on the original tightly closed containers in a dry, cool, well ventilated space, at temperatures between $5^{\circ}\text{C}$ - $40^{\circ}\text{C}$ ).   |  |
| PACKING              | Available in 5 L, 25L, 180L.  |  |
| FURTHER INFORMATION  | NA  |  |
| HEALTH SAFETY        | Please take the necessary measures in order to accomplish the national laws and regulations regarding the environmental, health and safety at work. Please observe the safety information displayed on the container. Please refer to the Safety Data Sheet for detailed information on the health, safety hazards and precautions for the use of this product. |  |

The information on this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. This is not a specification and all information is given in good faith. Every values presented as Theoretical were calculated from the product formula, so can have deviation from laboratory measurements using standard methods that may be not applicable. However, since the product can be used under conditions beyond our control, the manner of use is the sole responsibility of the user. The product is intended for professional use only. Manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. This Technical Data Sheet content can be changed without notice.

Parque Industrial de Carrascas, Estrada Nacional 252, 2950-402 Palmela PORTUGAL

◆ Tel.:+351 265107979

♦ www.globalnavy.net
♦ email: sales@globalnavy.net